NCP Series Dry Claw Vacuum Pumps

Models: NCP-30F, NCP-60F, NCP-80F, NCP-100F, NCP-105F, NCP-155F, NCP-255F2, NCP-305F2, NCP-405F, NCP-515F, NCP-1005F



Description: Dry Claw Vacuum Pump

Models: NCP-30F, NCP-60F, NCP-80F, NCP-100F,

NCP-105F, NCP-155F, NCP-255F2, NCP-305F2, NCP-405F, NCP-515F,

NCP-1005F
Power Range: 5 - 30 HP
Ultimate Vacuum Pressure:

Continuous: 150 TorrMaximum: 35 Torr

OVERVIEW

NES Company is proud to offer our NCP Series Dry Claw Vacuum Pumps, factory performance tested with a 1-year warranty against manufacturer's defects.

DESCRIPTION

NES Company Inc. introduces our latest line of vacuum pumps, the NCP Series. The NCP dry claw vacuum pump series is able to generate up to 35 torr at maximum and 150 torr in a continuous process at flow rates up to 671 CFM.

The NCP Series is carefully engineered and assembled with tight tolerances. Dry claw vacuum pumps exhibit the highest volumetric efficiency in CFM/HP ratios. Experience the difference that the NES Company NCP Series dry claw vacuum pumps provide for reliable, efficient, moderate vacuum processes.

FEATURES

- Pumping and gear chambers separated via labyrinth seals
- Synchronized timing gears within gear chamber for precision claw operation.
- Built-in anti-suck back valve prevents backflow upon shutdown.
- Accessories such as non-return valve, vacuum regulator, and exhaust silencer are available upon request.
- 1-year factory warranty against manufacturer's defects.



NOTES

NES Company is proud to offer our NCP Series Dry Screw Vacuum Pump. These dry claw vacuum pumps are factory performance tested and include a 1-year warranty against manufacturer's defects. Contact NES Company Inc. today to learn more about the series!

NCP Series Dry Claw Vacuum Pumps

Models: NCP-30F, NCP-60F, NCP-80F, NCP-100F, NCP-105F, NCP-155F, NCP-255F2, NCP-305F2, NCP-405F, NCP-515F, NCP-1005F



GENERAL TECHNICAL DATA (60 HZ)

NCP-F Air Cooled Units

Model	Capacity	Ult. Vac. Max.	Ult. Vac. Cont.	Power	Rotational Speed	Voltage	Noise Level	Oil Capacity	In/Out Connections	LxWxH	Ambient Operating Temperature
NCP-	CFM	Torr	Torr	HP	RPM	V	dB(A)	qt.	BSP (G)	in.	۰F
30F	32	50	37.5	1	1800		72	0.79	1/2"	29x13x18	
60F	42		75	2			80	0.63	1"	30x13x18]
80F	53		37.5	3			70	0.74	11/4"/1"	29x14x18	
100F	71		112.5	4		000	77	0.79		29x22x16	
105F	71		7.5	4		208-	75	0.40	1½"	32x17x21	
155F	106		75	5.5		230/460, 220-240	76	0.42		33x17x21	40 to 105
255F2	177	37.5		7.5	3600	/380-420.	76	0.05	2/1½"	38x20x27	40 10 103
305F2	211			10		400/690	77	0.85	2/1/2	39x20x27	
405F	282		150	12.5		400/090	70	4.50	0/01/"	44x23x28	
515F	353		150	15			78	1.58	3/2½"	51x23x28	
1005F	671			30			85	2.95	DN100 PN6/ DN100 PN10	60x29x41	

NCP-W Water Cooled Units

Model	Capacity	Ult. Vac. Max.	Ult. Vac. Cont.	Power	Rotational Speed	Voltage	Noise Level	Oil Capacity	In/Out Connections	LxWxH	Ambient Operating Temperature
NCP-	CFM	Torr	Torr	HP	RPM	>	dB(A)	qt.	BSP (G)	in.	°F
105W	71			4			75	0.42	1½"	32x17x21	
155W	106			5.5			76	0.42	1/2	33x17x21	
255W	176		< 22.5	7.5		208-	70				
305W	212	< 22.5		10	3600	230/460, 220-240	77	0.85	2/1½"	39x20x27	40 to
330W	230	< 22.5		10	3600	/380-420,	11				105
405W	282			12.5		400/690	78	1 50	3/2½"	44x23x28	
515W	353		< 75	15			/8	1.58	312/2	51x23x28	
1005W	671			30			85	2.95	100DN	58x31x50	

Model	Cooling Water Volume	Cooling Water Temperature				
NCP-	GPM	°F				
105W						
155W						
255W	> 0.53					
305W		a 77 (proformed) to 00				
330W		< 77 (preferred) to 86				
405W	> 1.06					
515W	7 1.00					
1005W	> 1.59					

NCP Series Dry Claw Vacuum Pumps

Models: NCP-30F, NCP-60F, NCP-80F, NCP-100F, NCP-105F, NCP-155F, NCP-255F2, NCP-305F2, NCP-405F, NCP-515F, NCP-1005F



Application table

Applications

Packaging

CNC Routing

Woodworking

Pneumatic Conveying

Holding & Lifting

Pick & Place Procedures

Medical Applications

Laboratory Applications

Plastics Industrial Processes

Central Vacuum Systems

... and more!

Accessories

Applications

Inlet Check Valve

Vacuum Regulator

Exhaust Silencer

Internal Coating