NDRV Series Dry-Running Rotary Vane Vacuum Pumps – Small Capacity

Models: NDRV-120, NDRV-140, NDRV-280, NDRV-480



Description: Dry Running Rotary Vane Vacuum Pumps – Small Capacity **Models:** NDRV-120, NDRV-140, NDRV-280, NDRV-480

Power Range: 0.16 - 1 HP Capacity Range: 4 - 17 CFM Ultimate Pressure: 27" Hg

OVERVIEW

NES Company is proud to offer our NDRV Series Dry Running Single Stage Rotary Vane Vacuum Pump. NES NDRV Series pumps are factory performance tested and include a 1-year warranty.

DESCRIPTION

NES Company Inc. introduces our latest line of single stage rotary vane vacuum pumps, the NDRV dry-running rotary vane vacuum pump series. These small pumps are able to generate levels of vacuum 27" Hg at flow rates between 4 and 17 CFM and 0.16 to 1 HP. The NDRV Series is meticulously machined and carefully crafted for tight tolerances resulting in low noise and low vibration designs that create a safe and comfortable environment for both pump and operator.

FEATURES

• Max vacuum pressure of 27" Hg for high vacuum applications.

• Low noise and low vibration levels for increased stability and comfort.

• Simple and sparse parts make for easy internal access and quick maintenance.

• Inlet port wire mesh dirt trap designed to sieve coarse particles.

• Cast or aluminum cast die constructed robust and compact pump.

 Oil lubrication acts as protective barrier for chamber and vanes

against friction and harsh process gasses.

• 1-year factory warranty against manufacturer's defects.



NOTES

NES Company Inc. NDRV Series dry-running single-stage rotary vane vacuum pumps are factory performance tested and include a 1-year warranty against manufacturer's defects.

NES Company Inc. 333 Route 46 West, Building A, Fairfield, NJ 07004

(800) 297-3550 | www.nescompany.com | info@nescompany.com

© 2023 NES Company Inc. All rights reserved

NDRV Series Dry-Running Rotary Vane Vacuum Pumps – Small Capacity



Models: NDRV-120, NDRV-140, NDRV-280, NDRV-480

GENERAL TECHNICAL DATA

Series Name	Nominal Speed (RPM)	Capacity CFM	Power [Ф/НZ/НР]	Motor Rating (Ф/НZ/VAC)	Ultimate Pressure (In. Hg Vac)	Sound Level (dB)
NDRV 120	3600	4	1/60/0.16	1/60/220	27	58
NDRV 140	1725 1725	5	1/60/0.34 3/60/0.75	1/60/220 1/60/220	27	58
NDRV 280	1725	10	1/60/0.75 3/60/1	3/60/220,380 1/60/220	27	68
NDRV 480		17	1/60/1	3/60/220,380	27	75

Application table

Applications				
Vacuum Packing				
Vacuum Printing				
Medical Instruments				
Vacuum Adhesion				
Vacuum Ovens & Furnaces				
Prosthetic Raw Material Degassing				
Resin Degassing				
Sputter & Deposition Systems				
Thin Film Coating				
Turbo Pump Backing				
Molding				
Power Plants				
Container Filling				
Filtering				
Extruder Venting				
Eviscerating				
Foods & Fats				

NES Company Inc. 333 Route 46 West, Building A, Fairfield, NJ 07004 (800) 297-3550 | www.nescompany.com | info@nescompany.com © 2023 NES Company Inc. All rights reserved

NDRV Series Dry-Running Rotary Vane Vacuum Pumps – Small Capacity

Models: NDRV-120, NDRV-140, NDRV-280, NDRV-480



Pump Weight

Series Name	Weight (Lb)
NDRV 120	20
NDRV 140	30
NDRV 280	56
	66
NDRV 480	

NES Company Inc. 333 Route 46 West, Building A, Fairfield, NJ 07004 (800) 297-3550 | www.nescompany.com | info@nescompany.com © 2023 NES Company Inc. All rights reserved